

POS PRINTER



SG-N80

Specifications

Printing

Printing method	Direct Thermal
Printing speed	160mm/s
Paper width	79.5 ± 0.5mm
Paper roll diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/ line or 512 dots/line
Character size	ANK
	Font A: 12×24 dots
	Font B: 9×17 dots
Line Space	3.75mm (Changeable by command)
Interface	USB / LAN / USB+Bluetooth
Print Command	Compatible with ESC/POS



Cutter

Auto Cut	Partial Cut
Cutter Life	1.5 Million cuts

Barcode

UPC-A/IPC-E/JAN13 (EAN13) /JAN8 (EAN8) /
CODABAR/ITF/CODE39/CODE93/CODE128

Code Page

PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、
PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、
West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、
PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、
PT151 (1251)

NV Flash

256K bytes

Input Buffer

64K bytes

Power

Power Source	DC 24V / 2.5A
Power Adapter	AC 110V~220V, 50~60Hz
Cash Drawer Output	DC 24V / 1A



QUOTATION

USD40.00 / piece or RMB265.00 / piece

MOQ: 200pcs

Term: FOB Guangzhou, China

If less than MOQ it will be EXW Guangzhou, China

Wall Hanging Support